

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : AeroShell Calibrating Fluid 2

Product code : 001A0032

CAS-No. : 64742-48-9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Special kerosine for aircraft fuel system calibration.
For further details consult the AeroShell Book on www.shell.com/aviation.

Recommended restrictions on use :

This product must be used, handled and applied in accordance with the requirements of the equipment manufacturer's manuals, bulletins and other documentation.

1.3 Details of the supplier of the safety data sheet

Company : Shell & Turcas Petrol A.Ş.
Salih Tozan Sk.No:18bbk Esentepe-Sisli
34394 Istanbul

Telephone : +902124441502

Telefax : +902123760600

E-mail address of person responsible for the SDS : If you have any enquiries about the content of this SDS please email lubricantSDS@shell.com

1.4 Emergency telephone number

Emergency telephone number : 0212 376 00 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification T.R. SEA No 28848

Flammable liquids , Category 3

H226: Flammable liquid and vapour.

Aspiration hazard , Category 1

H304: May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

Specific target organ toxicity - single exposure , Category 3, Narcotic effects.

H336: May cause drowsiness or dizziness.

Supplemental Hazard Statements

EUH066: Repeated exposure may cause skin dryness or cracking.

Classification T.R. SAE No 27092

R10: Flammable.

Harmful

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

2.2 Label elements

Labelling T.R. SEA No 28848

Hazard pictograms :



Signal word : Danger

Hazard statements :

H226

PHYSICAL HAZARDS:
Flammable liquid and vapour.

H304

HEALTH HAZARDS:
May be fatal if swallowed and enters airways.

H336

May cause drowsiness or dizziness.

ENVIRONMENTAL HAZARDS:
Not classified as environmental hazard according to CLP criteria.

Supplemental Hazard Statements : EUH066

Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243

Take precautionary measures against static discharge.

P261

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Response:

P301 + P310

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

P331

Do NOT induce vomiting.

Disposal:

P501

Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

Hazardous components which must be listed on the label:

Contains naphtha (petroleum), hydrotreated heavy.

Further information : Flammable.
Harmful:

2.3 Other hazards

May form flammable/explosive vapour-air mixture.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

High-pressure injection under the skin may cause serious damage including local necrosis.

SECTION 3: Composition/information on ingredients

3.1 Substances

Substance name : AeroShell Calibrating Fluid 2, 64742-48-9

Chemical nature : Naphtha (petroleum), hydrotreated heavy.

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	T.R. SAE No 27092	T.R. SEA No 28848	Concentration (%)
Naphtha (petroleum), hydrotreated heavy	64742-48-9 265-150-3	Xn; R10-R65- R66-R67	Flam. Liq.3; H226 Asp. Tox.1; H304 STOT SE3; H336 EUH066	<= 100

SECTION 4: First aid measures

4.1 Description of first aid measures

Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

If inhaled : Remove to fresh air. If rapid recovery does not occur, trans-

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

port to nearest medical facility for additional treatment.

In case of skin contact : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.
Obtain medical attention even in the absence of apparent wounds.

In case of eye contact : Flush eye with copious quantities of water.
If persistent irritation occurs, obtain medical attention.

If swallowed : If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.
Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.
Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters.

Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Potential for chemical pneumonitis.
Call a doctor or poison control center for guidance.

High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function.

Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding
Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Clear fire area of all non-emergency personnel.
Hazardous combustion products may include:
A complex mixture of airborne solid and liquid particulates and gases (smoke).
Carbon monoxide.
Unidentified organic and inorganic compounds.
Flammable vapours may be present even at temperatures below the flash point.
The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Will float and can be reignited on surface water.

5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Standard procedure for chemical fires.

Further information : Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe all relevant local and international regulations.
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
Local authorities should be advised if significant spillages

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

cannot be contained.
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Do not breathe fumes, vapour.
Do not operate electrical equipment.

6.2 Environmental precautions

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Ventilate contaminated area thoroughly.
If contamination of site occurs remediation may require specialist advice.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropri-

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

ate controls for safe handling, storage and disposal of this material.
Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling : Avoid inhaling vapour and/or mists.
Avoid contact with skin, eyes and clothing.
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
Bulk storage tanks should be diked (bunded).
When using do not eat or drink.

The vapour is heavier than air, spreads along the ground and distant ignition is possible.

Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed then seek immediate medical assistance.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Other data : Storage Temperature: Ambient.

Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions. Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., For container paints, use epoxy paint, zinc silicate paint.
Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.

7.3 Specific end use(s)

Specific use(s) : Please refer to Ch16 and/or the annexes for the registered

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

uses under REACH.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
CENELEC CLC/TR 50404 (Electrostatics – Code of practice for the avoidance of hazards due to static electricity).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Biological occupational exposure limits

No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

naphtha (petroleum), hydro-treated heavy : End Use: Workers
Exposure routes: Dermal
Value: 300 mg/kg/daylong term, systemic effects
End Use: Workers
Exposure routes: Inhalation
Value: 1500 mg/m³acute, systemic effects
End Use: Consumers
Exposure routes: Dermal
Value: 300 mg/kg/dayacute, systemic effects
End Use: Consumers
Exposure routes: Inhalation
Value: 900 mg/m³acute, systemic effects
End Use: Consumers
Exposure routes: Oral
Value: 300 mg/kg/dayacute, systemic effects

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.

8.2 Exposure controls

Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal protective equipment

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Skin and body protection : Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron.

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

Wear antistatic and flame retardant clothing, if a local risk assessment deems it so.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours [Type A boiling point >65°C (149°F)].

Protective measures : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation. Information on accidental release measures are to be found in section 6.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Liquid at room temperature.

Colour : colourless

Odour : Hydrocarbon

Odour Threshold : Data not available

pH : Not applicable

pour point : Data not available

Initial boiling point and boiling range : > 150 °C
estimated value(s)

Flash point : 43 °C
Method: Unspecified

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding
Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available
Upper explosion limit	:	Typical 6 %(V)
Lower explosion limit	:	0,6 %(V)
Vapour pressure	:	< 300 Pa (20 °C) estimated value(s)
Relative vapour density	:	> 5 estimated value(s)
Relative density	:	0,770 (15 °C)
Density	:	770 kg/m ³ (15,0 °C) Method: Unspecified
Solubility(ies)		
Water solubility	:	negligible
Solubility in other solvents	:	Data not available
Partition coefficient: n-octanol/water	:	Pow: > 3 (based on information on similar products)
Auto-ignition temperature	:	> 200 °C
Viscosity		
Viscosity, dynamic	:	Data not available
Viscosity, kinematic	:	0,95 mm ² /s (40,0 °C) Method: Unspecified
		1,15 mm ² /s (25 °C) Method: Unspecified
		1,46 mm ² /s (10 °C) Method: Unspecified
Explosive properties	:	Not classified
Oxidizing properties	:	Data not available

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

9.2 Other information

Conductivity	: Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10 000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid
Molecular weight	: 143 g/mol

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions
Stable under normal conditions of use.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

In certain circumstances product can ignite due to static electricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Hazardous decomposition products are not expected to form during normal storage., Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: Low toxicity:

Acute inhalation toxicity : LC 50 (Rat): Remarks: Low toxicity:
LC50 greater than near-saturated vapour concentration.

Acute dermal toxicity : LD 50 (Rabbit): > 5.000 mg/kg
Remarks: Low toxicity:

Skin corrosion/irritation

Product:

Remarks: Causes mild skin irritation.
Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Not irritating to eye.

Respiratory or skin sensitisation

Product:

Remarks: Not expected to be a sensitiser.

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: Not mutagenic.

Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.
Tumours produced in animals are not considered relevant to humans.

Material	GHS/CLP Carcinogenicity Classification
Naphtha (petroleum), hydro-treated heavy	No carcinogenicity classification.

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

Reproductive toxicity

Product:

Effects on fertility

:

Remarks: Not expected to be a developmental toxicant.
Not expected to impair fertility.

STOT - single exposure

Product:

Remarks: May cause drowsiness and dizziness.

STOT - repeated exposure

Product:

Remarks: Kidney: caused kidney effects in male rats which are not considered relevant to humans

Aspiration toxicity

Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Further information

Product:

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish (Acute toxicity) : Remarks: Expected to be not toxic at limit of water solubility.

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : Remarks: Expected to be not toxic at limit of water solubility.

Toxicity to algae (Acute toxicity) : Remarks: Expected to be not toxic at limit of water solubility.

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other : Remarks: Data not available

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

aquatic invertebrates (Chronic toxicity)

Toxicity to bacteria (Acute toxicity) : Remarks: Data not available

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Readily biodegradable.
Oxidises rapidly by photo-chemical reactions in air.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

12.4 Mobility in soil

Product:

Mobility : Medium: Water
Remarks: Floats on water.
Medium: Soil
Remarks: Adsorbs to soil and has low mobility.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

12.6 Other adverse effects

Product:

Additional ecological information : Remarks: Physical properties indicate that hydrocarbon gases will rapidly volatilise from the aquatic environment and that acute and chronic effects would not be observed in practice.

Remarks: Not expected to have ozone depletion potential.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water courses

Waste product should not be allowed to contaminate soil or water.

Contaminated packaging : Drain container thoroughly.
After draining, vent in a safe place away from sparks and fire.
Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.
Send to drum recoverer or metal reclaimer.
Comply with any local recovery or waste disposal regulations.

SECTION 14: Transport information

14.1 UN number

ADR : UN 1268

RID : UN 1268

IMDG : UN 1268

IATA : UN 1268

14.2 UN proper shipping name

ADR : PETROLEUM DISTILLATES, N.O.S.

RID : PETROLEUM DISTILLATES, N.O.S.

IMDG : PETROLEUM DISTILLATES, N.O.S.

IATA : PETROLEUM DISTILLATES, N.O.S.

14.3 Transport hazard class(es)

ADR : 3

RID : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

RID
Packing group : III

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding
Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3

IATA

Packing group : III
Labels : 3

14.5 Environmental hazards

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage,
for special precautions which a user needs to be aware of or
needs to comply with in connection with transport.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Not applicable
Ship type : Not applicable
Product name : Not applicable
Special precautions : Not applicable

Additional Information : MARPOL Annex 1 rules apply for bulk shipments by sea.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Regulations on the health and safety precautions for chemicals in the workplace. Regulations on the fire protection of buildings. Regulations on the prevention of industrial accidents and the reduction of their effects.

The components of this product are reported in the following inventories:

EINECS : All components listed or polymer exempt.

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

TSCA : All components listed.

SECTION 16: Other information

SDS Author

Name, Surname : Eda Demirer

Address : Shell & Turcas Petrol A.Ş. Derince Tesisleri
Deniz Mah. P.O Cad.
41900 Derince-Kocaeli

Certified Qualification date : 25 May 2015

Certificate number : GBF-1921

Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.

This product is classified as R65 (Harmful: may cause lung damage if swallowed) respectively H304 (May be fatal if swallowed and enters airways). The risk relates to potential for aspiration. The risk arising from aspiration hazard is solely related to the physico-chemical properties of the substance.

The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard. An exposure scenario is not presented.

This product is classified as R66 / EUH066 (Repeated exposure may cause skin dryness or cracking). The risk relates to the potential for repeated or prolonged dermal contact. The risk arising from contact is solely related to the physico-chemical properties of the substance. The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard and included within Chapter 8 of the SDS. An exposure scenario is not presented.

Revision changes: Revised according to regulation on Safety Data Sheets (SDSs) regarding hazardous substances and mixtures (R.G. 13/12/2014-29204)

Sources of key data used to : The quoted data are from, but not limited to, one or more

SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

AeroShell Calibrating Fluid 2

Initial release date: 06.02.2013

Revision Date: 29.05.2015

Version 1.5

MSDS Number: 800001005320

compile the Safety Data Sheet

sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TR / EN