

# SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## AeroShell Turbine Oil 500

Initial release date: 12.05.2010

Revision Date: 01.10.2015

Version 1.5

MSDS Number: 800001001487

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : AeroShell Turbine Oil 500

Product code : 001A0083

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Synthetic lubricating oil for aircraft turbine engines., For further details consult the AeroShell Book on [www.shell.com/aviation](http://www.shell.com/aviation).

Recommended restrictions on use : This product must be used, handled and applied in accordance with the requirements of the equipment manufacturer's manuals, bulletins and other documentation.  
This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

#### 1.3 Details of the supplier of the safety data sheet

Company : **Shell & Turcas Petrol A.Ş.**  
Karamancılar Is Merkezi Gulbahar Mh.  
Salih Tozan Sk.No:18bb1k Esentepe-Sisli  
TR-34394 Istanbul

Telephone : (+90) 2124441502

Telefax : (+90) 2123760600

E-mail address of person responsible for the SDS : If you have any enquiries about the content of this SDS please email [lubricantSDS@shell.com](mailto:lubricantSDS@shell.com)

#### 1.4 Emergency telephone number

Emergency telephone number : 0212 376 00 00

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification T.R. SEA No 28848

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

Chronic aquatic toxicity, Category 3

H412: Harmful to aquatic life with long lasting effects.

##### Classification T.R. SAE No 27092

Sensitising

R43: May cause sensitisation by skin contact.

# SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## AeroShell Turbine Oil 500

Initial release date: 12.05.2010

Revision Date: 01.10.2015

Version 1.5

MSDS Number: 800001001487

Dangerous for the environment

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### 2.2 Label elements

#### Labelling T.R. SEA No 28848

Hazard pictograms :



Signal word : Warning

Hazard statements :

H317

#### PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

#### HEALTH HAZARDS:

May cause an allergic skin reaction.

#### ENVIRONMENTAL HAZARDS:

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements :

#### Prevention:

P273

P280

Avoid release to the environment.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### Response:

P302 + P352

IF ON SKIN: Wash with plenty of water and soap.

P333 + P313

If skin irritation or rash occurs: Get medical advice/ attention.

#### Storage:

No precautionary phrases.

#### Disposal:

P501

Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

Contains N-phenyl-1-naphthylamine.

### 2.3 Other hazards

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

# SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding  
Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## AeroShell Turbine Oil 500

Initial release date: 12.05.2010

Revision Date: 01.10.2015

Version 1.5

MSDS Number: 800001001487

Chemical nature : Blend of synthetic esters and additives.

### Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	T.R. SAE No 27092	T.R. SEA No 28848	Concentration (%)
N-phenyl-1-naphthylamine	90-30-2 201-983-0	Xn-Xi-N; R22- R43-R50/53	Acute Tox.4; H302 Skin Sens.1B; H317 STOT RE2; H373 Aquatic Acute1; H400 Aquatic Chronic1; H410	0,5 - 2
Triaryl phosphate	1330-78-5 215-548-8	N; R50/53-R62	Repr.2; H361f Aquatic Acute1; H400 Aquatic Chronic1; H410	0,5 - 2

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : No treatment necessary under normal conditions of use.  
If symptoms persist, obtain medical advice.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.  
If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water.  
If persistent irritation occurs, obtain medical attention.
- If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Skin sensitisation (allergic skin reaction) signs and symptoms may include itching and/or a rash.  
Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.

# SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## AeroShell Turbine Oil 500

Initial release date: 12.05.2010  
Revision Date: 01.10.2015  
Version 1.5  
MSDS Number: 800001001487

Ingestion may result in nausea, vomiting and/or diarrhoea.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Notes to doctor/physician:  
Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide may be evolved if incomplete combustion occurs.  
Unidentified organic and inorganic compounds.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid contact with skin and eyes.

### 6.2 Environmental precautions

Environmental precautions : Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

# SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## AeroShell Turbine Oil 500

Initial release date: 12.05.2010

Revision Date: 01.10.2015

Version 1.5

MSDS Number: 800001001487

Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Advice on safe handling : Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

### 7.2 Conditions for safe storage, including any incompatibilities

Other data : Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.

Recommended storage temperature : -50 - 50 °C

Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Packaging material : Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.

# SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## AeroShell Turbine Oil 500

Initial release date: 12.05.2010

Revision Date: 01.10.2015

Version 1.5

MSDS Number: 800001001487

---

### 7.3 Specific end use(s)

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Biological occupational exposure limits

No biological limit allocated.

### 8.2 Exposure controls

#### Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

#### General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

#### Personal protective equipment

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

#### Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

# SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## AeroShell Turbine Oil 500

Initial release date: 12.05.2010

Revision Date: 01.10.2015

Version 1.5

MSDS Number: 800001001487

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

- Skin and body protection : Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron.
- Respiratory protection : No respiratory protection is ordinarily required under normal conditions of use.  
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.  
If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.  
Check with respiratory protective equipment suppliers.  
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.  
Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].
- Protective measures : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

### Environmental exposure controls

- General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.  
Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : Liquid at room temperature.

# SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## AeroShell Turbine Oil 500

Initial release date: 12.05.2010

Revision Date: 01.10.2015

Version 1.5

MSDS Number: 800001001487

---

Colour	:	Various colours
Odour	:	Slight hydrocarbon
Odour Threshold	:	Data not available
pH	:	Not applicable
pour point	:	<= -54 °C Method: Unspecified
Initial boiling point and boiling range	:	> 280 °C estimated value(s)
Flash point	:	256 °C Method: Unspecified
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available
Upper explosion limit	:	Typical 10 %(V)
Lower explosion limit	:	Typical 1 %(V)
Vapour pressure	:	< 0,5 Pa (20 °C) estimated value(s)
Relative vapour density	:	> 1 estimated value(s)
Relative density	:	1,005 (15 °C)
Density	:	1.005 kg/m <sup>3</sup> (15,0 °C) Method: Unspecified
Solubility(ies)		
Water solubility	:	negligible
Solubility in other solvents	:	Data not available
Partition coefficient: n-octanol/water	:	Pow: > 6 (based on information on similar products)
Auto-ignition temperature	:	> 320 °C



# SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## AeroShell Turbine Oil 500

Initial release date: 12.05.2010  
Revision Date: 01.10.2015  
Version 1.5  
MSDS Number: 800001001487

---

Viscosity  
Viscosity, dynamic : Data not available  
Viscosity, kinematic : 25,26 mm<sup>2</sup>/s (40,0 °C)  
Method: Unspecified  
5,17 mm<sup>2</sup>/s (100 °C)  
Method: Unspecified

### 9.2 Other information

Conductivity : This material is not expected to be a static accumulator.  
Decomposition temperature : Data not available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

### 10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

### 10.6 Hazardous decomposition products

Hazardous decomposition products are not expected to form during normal storage.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Information on likely routes of exposure : Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

#### Acute toxicity

#### Product:

# SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## AeroShell Turbine Oil 500

Initial release date: 12.05.2010

Revision Date: 01.10.2015

Version 1.5

MSDS Number: 800001001487

Acute oral toxicity : LD50 (rat): > 5.000 mg/kg  
Remarks: Expected to be of low toxicity:

Acute inhalation toxicity : Remarks: Not considered to be an inhalation hazard under normal conditions of use.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg  
Remarks: Expected to be of low toxicity:

### Skin corrosion/irritation

#### Product:

Remarks: Expected to be slightly irritating.  
Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

### Serious eye damage/eye irritation

#### Product:

Remarks: Expected to be slightly irritating.

### Respiratory or skin sensitisation

#### Product:

Remarks: Expected to be a skin sensitizer.

### Components:

#### **N-phenyl-1-naphthylamine:**

Remarks: May cause an allergic skin reaction in sensitive individuals.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vivo : Remarks: Not considered a mutagenic hazard.

### Carcinogenicity

#### Product:

Remarks: Not expected to be carcinogenic.

Material	GHS/CLP Carcinogenicity Classification
N-phenyl-1-naphthylamine	No carcinogenicity classification.
Triaryl phosphate	No carcinogenicity classification.

# SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## AeroShell Turbine Oil 500

Initial release date: 12.05.2010

Revision Date: 01.10.2015

Version 1.5

MSDS Number: 800001001487

---

### Reproductive toxicity

**Product:**

Effects on fertility

:

Remarks: Not expected to impair fertility.  
Not expected to be a developmental toxicant.

### STOT - single exposure

**Product:**

Remarks: Not expected to be a hazard.

### STOT - repeated exposure

**Product:**

Remarks: Not expected to be a hazard.

### Aspiration toxicity

**Product:**

Not considered an aspiration hazard.

### Further information

**Product:**

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.

ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

**Product:**

Toxicity to fish (Acute toxicity) : Remarks: Expected to be harmful:  
LL/EL/IL50 10-100 mg/l

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : Remarks: Expected to be harmful:  
LL/EL/IL50 10-100 mg/l

Toxicity to algae (Acute toxicity) : Remarks: Expected to be harmful:  
LL/EL/IL50 10-100 mg/l

# SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## AeroShell Turbine Oil 500

Initial release date: 12.05.2010

Revision Date: 01.10.2015

Version 1.5

MSDS Number: 800001001487

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

Toxicity to bacteria (Acute toxicity) : Remarks: Data not available

### **Components:**

#### **N-phenyl-1-naphthylamine:**

M-Factor (Acute aquatic toxicity) : 1

## 12.2 Persistence and degradability

### **Product:**

Biodegradability : Remarks: Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but contains components that may persist in the environment.

## 12.3 Bioaccumulative potential

### **Product:**

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

## 12.4 Mobility in soil

### **Product:**

Mobility : Remarks: Liquid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be mobile.

Remarks: Floats on water.

## 12.5 Results of PBT and vPvB assessment

### **Product:**

Assessment : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB..

## 12.6 Other adverse effects

### **Product:**

Additional ecological information : Remarks: Product is a mixture of non-volatile components, which are not expected to be released to air in any significant

# SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## AeroShell Turbine Oil 500

Initial release date: 12.05.2010

Revision Date: 01.10.2015

Version 1.5

MSDS Number: 800001001487

quantities.

Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

Remarks: Poorly soluble mixture.

May cause physical fouling of aquatic organisms.

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

---

### SECTION 14: Transport information

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

#### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

# SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## AeroShell Turbine Oil 500

Initial release date: 12.05.2010

Revision Date: 01.10.2015

Version 1.5

MSDS Number: 800001001487

---

Pollution category	: Not applicable
Ship type	: Not applicable
Product name	: Not applicable
Special precautions	: Not applicable

**Additional Information** : MARPOL Annex 1 rules apply for bulk shipments by sea.

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Regulations on the health and safety precautions for chemicals in the workplace. Regulations on the fire protection of buildings. Regulations on the prevention of industrial accidents and the reduction of their effects.

**The components of this product are reported in the following inventories:**

EINECS : All components listed or polymer exempt.

TSCA : All components listed.

---

### SECTION 16: Other information

#### Full text of R-Phrases

R22 : Harmful if swallowed.  
R43 : May cause sensitisation by skin contact.  
R50/53 : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R62 : Possible risk of impaired fertility.

#### Full text of H-Statements

H302 : Harmful if swallowed.  
H317 : May cause an allergic skin reaction.  
H361f : Suspected of damaging fertility.  
H373 : May cause damage to organs through prolonged or repeated exposure if swallowed.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Acute aquatic toxicity  
Aquatic Chronic : Chronic aquatic toxicity  
Repr. : Reproductive toxicity

# SAFETY DATA SHEET

Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

## AeroShell Turbine Oil 500

Initial release date: 12.05.2010

Revision Date: 01.10.2015

Version 1.5

MSDS Number: 800001001487

Skin Sens. : Skin sensitisation  
STOT RE : Specific target organ toxicity - repeated exposure

### SDS Author

Name, Surname : Eda Demirer

Address : Shell & Turcas Petrol A.Ş. Derince Tesisleri  
Deniz Mah. P.O Cad.  
41900 Derince-Kocaeli

Certified Qualification date : 25 May 2015

Certificate number : GBF-1921

### Further information

Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.

Revision changes: Revised according to regulation on Safety Data Sheets (SDSs) regarding hazardous substances and mixtures (R.G. 13/12/2014-29204)

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TR / EN